



ECO-BOND Adhesives, LLC  
 1343 E. Wisconsin Ave. #110  
 Pewaukee, WI 53072  
 800-326-8102  
[www.ecobondit.com](http://www.ecobondit.com)

# Kitchen-Bath-Tile

## Non-Toxic Caulk, Construction Adhesive, Sealant, and Silicone Replacement

### PRODUCT SPECIFICATIONS:

- Zero VOC's off gassed during curing process
- 100% NON-Toxic, no solvents
- AAMA Certified
- Waterproof
- Non-Yellowing
- Certified Hypoallergenic
- Bonds & Seals Fully Submerged
- Exceeds all CA Standards
- Chemically impervious to all mold and mildew
- No toxic odor
- Paintable within in 2 hours
- Application Temperature is -35° to +140° F
- No Prop 65 listed materials
- UV resistant
- Earns LEED and NAHB Green Building Points
- Non-Shrinking
- Safe to use indoors
- Non-Flammable
- Non-petroleum based
- Compatible with SBS Flashing

### TECHNICAL SPECIFICATIONS:

- Tensile strength: 200 psi
- Elongation: 300% - 400%
- Shore A Hardness: 35 +/- 5
- Skin Time: Less than 20 minutes @ 77 degF/ 50% RH
- Tack Free Time: Less than 1 hour @77 degF/ 50% RH
- Cure Rate: 1/4" Bead per 24 Hrs
- Movement Capability: 25%
- UV Rating: No discoloration or change in appearance after 2500 hrs. of UV
- Application Temperature is -35° to +140°
- Sag: None
- Staining: None

### BONDS & SEALS TO:

Aluminum	Paneling
Brick	Plaster
Cement Board	Plastic
Ceramic	Plywood
Concrete	Porcelain
Copper	PVC
Drywall	Rubber
Foam	Steel
Glass	Tile
Granite	Tub Surrounds
Laminate	Two Non-porous Surfaces
Marble	
Metal	Vinyl
Mirrors	Windows
Painted Surfaces	Wood

### PERFORMANCE STANDARDS:

- ASTM C-920
- Meets CA requirements for Prop 65 and all Clean Air Standards
- ASTM D-1002TT-S-00230 Type II, Class A, Corp of Engineers
- AAMA 808.3-92 Exterior Perimeter Sealing

### STOCK SIZES:

- 10.1 Ounce Tube

### SPECIAL ORDER:

- 2 ounce, 29 ounce, 2 Gallon, 5 Gallon & 55 Gallon
- Color matching available

# 1-800-ECO-8102

[www.ecobondit.com](http://www.ecobondit.com)