



ECO-BOND Adhesives, LLC
 1343 E. Wisconsin Ave. #110
 Pewaukee, WI 53072
 800-326-8102
www.ecobondit.com

Windows- Doors-Trim

Non-Toxic Caulk, Construction Adhesive, Sealant, and Silicone Replacement

PRODUCT SPECIFICATIONS:

- Zero VOC's off gassed during curing process
- 100% NON-Toxic, no solvents
- AAMA Certified
- Waterproof
- Certified Hypoallergenic
- Bonds & Seals Fully Submerged
- Exceeds all CA Standards
- Chemically impervious to all mold and mildew
- No toxic odor
- Paintable within in 2 hours
- Tack Free 45 minutes
- Application Temperature is -35° to +140° F
- No Prop 65 listed materials
- UV resistant
- Earns LEED and NAHB Green Building Points
- Non-Shrinking
- Safe to use indoors
- Non-Flammable
- Non-petroleum based
- Easy to tool
- Compatible with SBS Flashing

PERFORMANCE STANDARDS:

- Exceeds the requirements of ASTM C920, Type S, Grade NS, Class 50, Use T, NT, M, and G
- Federal Specifications TT-S-00230C, Type II, Class A
- Meets California Requirements for Prop 65 and All Clean Air Act Standards

TECHNICAL SPECIFICATIONS:

- Shear strength: 190 psi
- Tensile strength: 200 psi
- Elongation: 300% - 400%
- Cure Rate: 1/4" Bead per 24 Hrs
- Movement Capability: 25%
- UV Rating: No discoloration or change in appearance after 2500 hrs. of UV
- Sag: None
- Staining: None

BONDS & SEALS TO:

- | | |
|-----------------------|-------------------------|
| Aluminum | Plywood |
| Block and Brick | Polystyrene |
| Cement Based Products | Polyurethane |
| Coated Metal | PVC |
| Concrete | Resins |
| Cork | Rubber |
| Drywall | Sheet Metal |
| Fiberglass | Siding |
| Foam | Slate |
| Galvanized Metal | Steel |
| Glass | Stone |
| Laminate | Stucco |
| Marble | Tile |
| Metal | Treated Wood |
| Mirrors | Two Non-porous Surfaces |
| Painted Surfaces | Vinyl |
| Paneling | Windows |
| Plaster | Wood |
| Plastics | |

STOCK SIZES:

- 10.1 Ounce Tube

SPECIAL ORDER:

- 2 ounce, 29 ounce, 2 Gallon, 5 Gallon & 55 Gallon
- Color matching available

1-800-ECO-8102

www.ecobondit.com