



ECO-BOND Adhesives, LLC  
1343 E. Wisconsin Ave. #110  
Pewaukee, WI 53072  
800-326-8102  
[www.ecobondit.com](http://www.ecobondit.com)

**Ultra-Clear**

## Non-Toxic Caulk, Construction Adhesive, Sealant, and Silicone Replacement

### PRODUCT SPECIFICATIONS:

- Zero VOC's off gassed during cure process
- 100% NON-Toxic
- No Solvents
- Waterproof
- Non-Yellowing
- Certified Hypoallergenic
- Bonds & Seals Fully Submerged
- Exceeds all CA Standards
- Chemically impervious to all mold and mildew
- No toxic odor
- Paintable
- Application Temperature is -35° to +140° F
- No Prop 65 listed materials
- UV resistant
- Earns LEED and NAHB Green Building Points
- Non-Shrinking
- Safe to use indoors
- Non-Flammable
- Non-petroleum based

### PERFORMANCE STANDARDS:

- ASTM C920, Type S, Grade NS, Class 25, Use NT, T, M, G, A and O
- Federal Specifications TT-S-00230C, Type II, Class A
- CAN/CGSB-1913-M82
- AAMA 808.3-92 Exterior Perimeter Sealing

### TECHNICAL SPECIFICATIONS:

- Shear strength: 200 psi
- Tensile strength: 250 psi
- Peel strength: 22 pli
- Elongation: 450% - 500%
- Skin Time: Less than 20 minutes @ 77 degF/ 50% RH
- Cure Rate: 1/4" Bead per 24 Hrs
- Movement Capability: 25%
- UV Rating: No discoloration or change in appearance after 2500 hrs. of UV
- Application Temperature is -35° to +140°
- Sag: None
- Staining: None

### BONDS & SEALS TO:

Aluminum	Plaster
Asphalt	Plastics
Block and Brick	Plywood
Cement Based Products	Polystyrene
Ceramic	Polyurethane
Coated Metal	Porcelain
Concrete	PVC
Copper	Resins
Cork	Rubber
Drywall	Sheet Metal
Fiberglass	Siding
Foam	Slate
Galvanized Metal	Steel
Glass	Stone
Granite	Stucco
Kynar 500	Tile
Laminate	Treated Wood
Marble	Tub Surrounds
Metal	Two Non-porous Surfaces
Mirrors	Vinyl
Painted Surfaces	Wood
Paneling	

### STOCK SIZES:

- 10.1 Ounce Tube

### SPECIAL ORDER:

- 2 ounce, 29 ounce, 2 Gallon, 5 Gallon & 55 Gallon

**1-800-ECO-8102**

**[www.ecobondit.com](http://www.ecobondit.com)**